

REDYPLAST

Shri Ashoka Pipe & Fitting Centre
Technical data sheet · Lay Flat Tubes

R-FLEX LAY FLAT SUBLINE TUBE 75 MM

flexible Lay Flat Tube/Submain pipe/Subline pipe 75 MM

Specifications

SKU	RDP-LFT-BK-75
Model	RDP2071
Category	Lay Flat Tubes
Size / bore	75 MM
Length	60 M
Wall thickness	1000 MICRON
Operating pressure	2 to 4 kg/cm ²
Colour	BLACK
Material	HDPE
Shipping weight	13000 GRAM
HSN code	84248200
Origin	Made in India
Minimum order quantity	1 piece
Standard packing	2 pieces per box
Availability	In stock
Units in stock	50

Features

- flexible subline/submain pipe
- cost effective
- UV resistant
- durable
- standwith tough weather conditions
- eco friendly
- easy to install
- used over the surface

Applications

- Pump to field delivery on rented or fragmented plots
- Feeding a sprinkler or rain-hose block from a distant source
- Temporary mains while a permanent line is being laid
- Moving water across a bund or field boundary

MRP per piece	INR 4,140
Full box of 2	INR 8,280

MRP is per piece and inclusive of tax (5% GST). Orders are placed in pieces from the minimum order quantity above; the box is packaging, not a required