

REDYPLAST

Technical data sheet · Lay Flat Tubes

R-FLEX LAY FLAT SUBLINE TUBE 90 MM

Flexible HDPE lay-flat subline tube for surface water delivery and irrigation applications

Specifications

SKU	RDP-LFT-BK-90
Model	RDP2072
Category	Lay Flat Tubes
Size / bore	90 MM
Length	60 M
Wall thickness	1000 MICRON
Operating pressure	2 to 4 kg/cm ²
Colour	BLACK
Material	HDPE
Shipping weight	16200 GRAM
HSN code	84248200
Origin	Made in India
Minimum order quantity	1 piece
Standard packing	2 pieces per box
Availability	In stock
Units in stock	20

Features

- Flexible HDPE lay-flat construction
- Suitable for subline and submain water delivery
- 1000 micron wall thickness
- 60-meter approximate length
- 2–4 kg/cm² specified operating pressure
- Easy to roll and store when drained
- Suitable for surface installation
- Available in 63 MM, 75 MM and 90 MM sizes

Applications

- Pump-to-field water delivery
- Irrigation on rented or fragmented agricultural plots
- Feeding sprinkler and rain-hose systems
- Temporary surface water mains
- Moving water across field boundaries and bunds
- Garden and landscaping water delivery
- Temporary or movable irrigation layouts

MRP per piece	INR 4,860
Full box of 2	INR 9,720

MRP is per piece and inclusive of tax (5% GST). Orders are placed in pieces from the minimum order quantity above; the box is packaging, not a required quantity.

